



A 33,5 B 75 (mm)

## Link

### Technical specification

Linear led light with built in electronic gear. Housing of powder painted extruded aluminum for optimal cooling. Serial connection possible with easy Plug-in system for a continuous row of light. Link is easy and quick to install.

**Model and colors** Available in black.

**Area of use** Linear led light for indoor applications, suitable for general or decoration lighting. Choose between recessed, suspended or ceiling mounted.

### Technical data

|                       |                                    |
|-----------------------|------------------------------------|
| Mains (input) voltage | 220-240 V                          |
| Total weight          | 1,2 kg/ 2.2 kg/ 3 kg/ 3.5 kg/ 4 kg |
| Form of protection    | IP 20, class I                     |
| Light source          | LED                                |
| Operating position    | Horizontal                         |
| Start time            | Instant                            |
| Driver                | Built in                           |
| Optics                | Opaque diffuser                    |

| Art no      | Description                            | Color |
|-------------|--|-------|
| 307-535-20  | L 934mm 830                            | Black |
| 307-500-20  | L 1650mm 830                           | Black |
| 307-510-20  | L 2150mm 830                           | Black |
| 307-520-20  | L 2400mm 830                           | Black |
| 307-530-20  | L 2900mm 830                           | Black |
| 047-273     | Wire suspension kit, 4m                | -     |
| 047-180-xx  | Track clip white for threaded rod/wire | -     |
| 307-211-001 | Recessed bracket kit                   | -     |
| 307-203-001 | Locking device for serial connection   | -     |

| Type          | Delivered lumen output (lm) | System power (W) | EEI <sup>3</sup> |
|---------------|-----------------------------|------------------|------------------|
| 830<br>934mm  | 1800                        | 16,3             | A+               |
| 840<br>934mm  | 1900                        | 16,3             | A++              |
| 830<br>1650mm | 3100                        | 29               | A+               |
| 840<br>1650mm | 3300                        | 29               | A++              |
| 830<br>2150mm | 4000                        | 37,5             | A+               |
| 840<br>2150mm | 4200                        | 37,5             | A++              |
| 830<br>2400mm | 4500                        | 42               | A+               |
| 840<br>2400mm | 4700                        | 42               | A++              |
| 830<br>2900mm | 5400                        | 50               | A+               |
| 840<br>2900mm | 5600                        | 50               | A++              |

### Note

Wire suspensions kit or recessed bracket kit is ordered separate.

Final shipping destination may require minor modifications of components as well as article numbers, be sure to state the country in which the fixtures will be used.